



OKS 1301 - Product Information

Fields of Application:

Sliding coating of materials of all kinds, such as metals, glass, ceramic, wood, leather and plastics (check solvent compatibility). As lubricant for threads of all kinds, such as machine screws, thread-cutting screws, sheet-metal and wood screws for increasing pre-tension forces or reducing screw-in torques. As dry lubricant for maintenance and care of plastic/metal sliding pairs. For assembly of axial face seals or dry lubrication in textile or paper-processing machines.





OKS 1301 Sliding Film, colourless, Spray

Advantages and Benefits:

Highly effective due to outstanding film-forming properties. Excellently suited for producing non-slip dry, non-soiling sliding films on a wide range of materials. Broad range of uses for dry lubrication in maintenance and care. Waterproof and resistant to weathering.

Application:

For optimum adhesion clean surfaces, first mechanically and then with OKS 2610/OKS 2611 Universal Cleaner. The surfaces must be metallic bright and dry. Shake well before use. Spray a thin layer evenly from 20 - 30 cm distance to the prepared surface. Drying conditions acc. to the following technical data. For further questions please contact our Technical Department.



Additional Information:

Packaging (Article number):
- 400 ml Spray (01301004)

Version:
E-12.1/08

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. ® = Registered Trademark



OKS 1301 Sliding Film, colourless, Spray

Technical Data

	Norm	Conditions	Unit	Value
Solid Lubricants				
Type				Synthetic wax
Solvents				
Type				Special boiling point gasoline
Film layer				
Application temperature				Room temperature
Drying time		+20°C	h	0,1
Surface coverage			m ² /Tin	2 - 3
Application Data				
Density	DIN EN ISO 3838	+20°C	g/ml	0,66
Colour				colourless
Service Temperatures				
Minimum service temperature			°C	-60
Maximum service temperature			°C	100
Friction Values				
Thread friction value	DIN EN ISO 16047	Screw: ISO 4017 M10x55-8.8 plain Nut: ISO 4032 M10-10 plain	μ	0,08 - 0,1

The data in this brochure are the result of extensive testing and experience and meet the latest stage of engineering. Due to the diversity of application possibilities and technical realities they can only be recommendations and are not arbitrarily transferable; thus no obligations, liability or warranty claims can be derived herefrom. We accept liability for the fitness of our products for particular purposes and accept such liability in writing in the individual case. In any event any justified warranty claims shall be limited to the delivery of replacement goods which are free from defect or, in the event that such subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular but without limitation any liability for consequent damage, shall be excluded. Prior to use own testing must be done to prove suitability. The data are subject to change for the sake of technical progress. © = Registered Trademark